



## 325 - 330 Wp

**25**  
YEARS  
**85%**



## AXIworldpower


72 cell polycrystalline  
High performance solar module

### The advantages:

- 15** Years 15 years manufacturer's warranty
- P-Max** Highest performance due to specifically selected technologies and materials
- +** Wp Guaranteed positive power tolerance from 0-5 Wp by individual measurement
- ↓** 2.400 Pa Maximum 2400 Pa snow load
- 100%** 100% electroluminescence inspection
- IP 67** High quality junction box and connector systems

### Exclusive linear AXITEC high performance guarantee!

- 15 years manufacturer's guarantee on 90% of the nominal performance
- 25 years manufacturer's guarantee on 85% of the nominal performance



## AXIworldpower 325 - 330 Wp

**Electrical data** (at standard conditions (STC) irradiance 1000 watt/m<sup>2</sup>, spectrum AM 1,5 at a cell temperature of 25°C)

Type	Nominal output P <sub>mpp</sub>	Nominal voltage U <sub>mpp</sub>	Nominal current I <sub>mpp</sub>	Short circuit current I <sub>sc</sub>	Open circuit voltage U <sub>oc</sub>	Module conversion efficiency
AC-325P/72S	325 Wp	37,66 V	8,63 A	9,15 A	45,92 V	16,83 %
AC-330P/72S	330 Wp	37,82 V	8,73 A	9,28 A	46,97 V	17,08 %

### Design


Frontside	3,2 mm hardened, low-reflection white glass
Cells	72 polycrystalline high efficiency cells 156,75 mm x 156,75 mm (6")
Backside	Composite film
Frame	40 mm silver aluminium frame

### Mechanical data

L x W x H	1957 x 987 x 40 mm
Weight	21,5 kg with frame

### Power connection

Socket	Protection Class IP67 (3/6 bypass diodes)
Wire	approx. 1,2 m, 4 mm <sup>2</sup>
Plug-in system	Plug/socket IP67



All dimensions in mm

### Limit values

System voltage	1000 VDC
NOCT (nominal operating cell temperature)*	45°C +/-2K
Max. load-carrying capacity	2400 N/m <sup>2</sup>
Reverse current feed IR	15,0 A
Permissible operating temperature	-40°C to 85°C / -40F to 185F

(No external voltages greater than U<sub>oc</sub> may be applied to the module)

\* NOCT, irradiance 800 W/m<sup>2</sup>; AM 1,5;  
wind speed 1 m/s; Temperature 20°C

### Temperature coefficients

Voltage U <sub>oc</sub>	-0,30 %/K
Current I <sub>sc</sub>	0,04 %/K
Output P <sub>mpp</sub>	-0,40 %/K

### Low-light performance

 (Example for AC-320P/72S)

I-U characteristic curve	Current I <sub>pp</sub>	Voltage U <sub>pp</sub>
200 W/m <sup>2</sup>	1,80 A	35,97 V
400 W/m <sup>2</sup>	3,07 A	35,99 V
600 W/m <sup>2</sup>	5,51 A	36,91 V
800 W/m <sup>2</sup>	6,95 A	37,32 V
1000 W/m <sup>2</sup>	8,52 A	37,56 V